

ORD9215 Reed Switch

Ultra-miniature

- The ORD9215 is a small single-contact reed switch designed for general control of medium level loads less than 100 V. The contacts are sealed within the glass tube with inert gas to maintain contact reliability.



ORD9215 Ultra-miniature

Applications

- Control equipment
- Communication equipment
- Measurement equipment
- Household appliances


Features

- Reed contacts are hermetically sealed within a glass tube with inert gas and do not receive any influence from the external atmospheric environment.
- Quick response
- The structure comprises the operating parts and electrical circuits arranged coaxially. Reed switches are suited to applications in radio frequency operation.
- Reed switches are compact and light weight.
- Superior corrosion resistance and wear resistance of the contacts assures stable switching operation and long life.
- With a permanent magnet installed, reed switches economically and easily become proximity switches.

Electrical Characteristics

Parameter	Rated Value	Unit
Pull-In Range	10~50	AT
Drop-Out (min.)	4	AT
Contact Resistance (max.)	100	mΩ
Breakdown Voltage (min.)	150	VDC
Insulation Resistance (min.)	10 ⁹	Ω
Electrostatic Capacitance (max.)	0.3	pF
Contact Rating	10	VA
Switching Voltage (max.)	100 DC/ AC	V
Switching Current (max.)	0.5	A
Carry Current (max.)	1.0	A

Dimensions (mm)




Operating Characteristics

Parameter	Rated Value	Unit
Operate Time (max.)	0.4	ms
Bounce Time (max.)	0.4	ms
Release Time (max.)	0.05	ms
Resonant Frequency	3700±400	Hz
Operating Frequency (max.)	500	Hz


ORD9215 Reed Switch

ELECTRICAL CHARACTERISTICS


Pull-in Value vs. Drop-out Value




Contact resistance




Breakdown voltage



Insulation resistance




Electrostatic capacitance




ORD9215 Reed Switch

OPERATING CHARACTERISTICS


Operate time




Bounce time



Release time





Resonant frequency




ORD9215 Reed Switch

MECHANICAL CHARACTERISTICS



ENVIRONMENTAL CHARACTERISTICS


Parameter	Rated Value	Unit
Temperature range	-40 to +125	°C
Shock (11ms)	294 (30G)	m/s ²
Vibration (10~2000Hz)	196 (20G)	m/s ²
Lead tensile strength	19.6 (2kgf)	N




ORD9215 Reed Switch

ENVIRONMENTAL CHARACTERISTICS


Temperature cycle




Temperature and humidity cycle



High temperature storage test




Low temperature storage test




ORD9215 Reed Switch

ENVIRONMENTAL CHARACTERISTICS


Shock test (Electrical characteristics)



Shock test (Misoperation area)



Vibration test



Please note: All technical specifications on this datasheet refer to the standard product range. Modifications in the sense of technical progress are reserved. For general information only. For more specific information, please consult the product datasheet, available upon request.

This datasheet could contain technical inaccuracies or typographical errors. Changes are periodically made to the information herein. These change will be incorporated in future revisions.

For deviating values, most current specifications and products please contact your nearest sales office.